

## HDMI to SDI Instruction

### 1. Product introduction:

- (1) No compression, no delay instant HD distribution output.
- (2) Professional video amplification IC chip design scheme.
- (3) Support 1080P input, compatible with the following.
- (4) SDI output, output resolution is adjustable.
- (5) Professional broadcasting standards.
- (6) External DC 5V power supply, high stability.
- (7) Long transmission distance, no signal attenuation.
- (8) One-way video signal input, four-way video signal output.

### 2. Product parameters:

Name	Parameters
Input interface	1 HDMI signal
Output interface	1 SDI HD video signal
Video loop out	SDI HD video signal
Interface	Standard BNC
Power consumption	Full load 1W
Power supply	External 5V DC
Chassis structure	Aluminum wire drawing
Product size	100*93*21mm

Dip switch	Output resolution
111	1080P60
011	1080P50
001	1080P25
000	720P50
010	1080I50
110	1080I60
101	1080P30
100	720P60

### 3. Function introduction:

- DC 5V ➡ Connect the power adapter.
- HDMI IN ➡ Connect the HDMI monitor.
- SDI OUT ➡ Connect the SDI monitor or matrix.
- SDI OUT ➡ Connect the SDI monitor or matrix.
- SET ➡ Output resolution adjustment.



### 4. Shipping lists:

1	2	3	4
A host PC	A power adapter	Instruction	Certificate