

SDI to HDMI Instruction

1. Product introduction:

- | | |
|---|---|
| <ul style="list-style-type: none"> (1) No compression, no delay instant HD distribution output. (2) Professional video amplification IC chip design scheme. (3) Support SD, HD, 3G. (4) Support one power cut through function. (5) Professional broadcasting standards. | <ul style="list-style-type: none"> (6) External DC 5V power supply, high stability. (7) Long transmission distance, no signal attenuation. (8) One-way video signal input, four-way video signal output. |
|---|---|

2. Product parameters:

Name	Parameters
Input interface	1 SDI signal
Output interface	1 HDMI signal
Video loop out	SDI HD video signal
Interface	Standard BNC
Power consumption	Full load 1W
Power supply	External 5V DC
Chassis structure	Aluminum wire drawing
Product size	100*93*21mm

Dip switch	Output resolution
111	1080P60
011	1080P50
001	1080P25
000	720P50
010	1080I50
110	1080I60
101	1080P30
100	720P60

3. Function introduction:

- DC 5V
➡
Connect the power adapter.
- HDMI OUT
➡
Connect the HDMI monitor.
- SDI IN
➡
Connect the SDI video signal source.
- SDI OUT
➡
Connect the SDI monitor or matrix.
- SET
➡
Output resolution adjustment.



4. Shipping lists:

1	2	3	4
A host PC	A power adapter	Instruction	Certificate